



Valli Granulati s.r.l.  
24060 ZANDOBBIO (BG) - Italia - Via Selva, 20 - Tel. 035 940249 - Fax 035 943256  
www.valligranulati.it - info@valligranulati.it - Partita I.V.A. e Codice Fiscale IT01624170161 - Cap. Soc. € 100.000,00 i.v.  
R.E.A. Bergamo n. 223742 - Iscr. Albo Impr. Artig. Bergamo n. 86340 - Export BG 019845 - Iscr. Imprese Bergamo n. 01624170161

# VALLIMIX

## DATA SHEET

### DESCRIPTION

VALLIMIX premixed quartz coating is based on quartz for the protection and finish of Industrial floors with excellent resistance to abrasion. For concrete substrates is applied manually or with machines distribution, with the method of the "fresh on fresh." For interior and exterior floors with medium to heavy traffic.

### APPLICATION

The application can be done manually or with special vending machines, making sure to cover the concrete substrate with a constant amount of VALLIMIX: from 3 kg to 6 kg per sqm.

### WARNINGS

- ✓ Run applications with temperatures between + 5 ° C and + 30 ° C.
- ✓ Do not apply in full sun and strong winds.
- ✓ In hot weather it is advisable to protect the floors run for at least a couple of days with protective waterproof sheets, moistening the surfaces with water treated in the days following the execution of the floor.
- ✓ Make sure before the hardener pose, the correct composition and performance characteristics of the concrete supplied for the execution of the Industrial floor.
- ✓ The premix contains dust. Handling we recommend the use of suitable masks.

### TECHNICAL FEATURES

Appearance	Powder
Color	Grey, red, tobacco, green, black, anthracite
Bulk density powder	1450 kg / m <sup>3</sup>
Particle size	2.5 mm
Aggregate	national Quartz
SiO <sub>2</sub> content of aggregate	> 96%
aggregate hardness	> 7 Mohs scale
Packaging Paper bags	25 kg

### STORAGE

- 6 months in original packaging intact and protected from humidity



Valli Granulati s.r.l.  
24060 ZANDOBBIO (BG) - Italia - Via Selva, 20 - Tel. 035 940249 - Fax 035 943256  
www.valligranulati.it - info@valligranulati.it - Partita I.V.A. e Codice Fiscale IT01624170161 - Cap. Soc. € 100.000,00 i.v.  
R.E.A. Bergamo n. 223742 - Iscr. Albo Impr. Artig. Bergamo n. 86340 - Export BG 019845 - Iscr. Imprese Bergamo n. 01624170161



**VALLI GRANULATI SRL VIA SELVA, 20 24060 ZANDOBBIO (BG)**  
**18**

**UNI EN 13813:2004**

**MASSETTO CEMENTIZIO (CT) per utilizzo sia all'esterno che all'interno degli edifici.**

Reazione al fuoco	classe A1 <sub>fl</sub>
Rilascio di sostanze corrosive:	CT
Permeabilità all'acqua:	NPD
Permeabilità al vapore acqueo:	NPD
Resistenza alla compressione:	C40
Resistenza alla flessione:	F6
Resistenza all'usura:	A12
Isolamento al suono:	NPD
Assorbimento del suono:	NPD
Resistenza termica:	NPD
Resistenza chimica:	NPD

nr. DOP : **MAS-2018-10**

Per esigenze produttive alcuni dati riportati sul sacco (ad es. : il nr. della DOP, ecc.) potrebbero non essere aggiornati. Tutti i dati aggiornati (compreso il nr. della DOP riferita al lotto di produzione, identificato dalla data impressa sull'imballo) sono disponibili sul sito internet del produttore: [www.valligranulati.it](http://www.valligranulati.it)